

Specifications

- Single- or double-acting cylinder control
- Working pressure 700 bar
- Max flow rate 25 l/min
- Manual control with spring return or indexed manual control
- Electro-magnetic return 12V - 24V - 107V - 196 V - 50Hz
- Base mounting
- Assembly plan on request



WV 700 series control valves - 2/2				
Function	Electromagnetic control	Electromagnetic HR manual	HF manual control	Neutral position
2/2 WS				P to T
2/2 WO				All locked
2/2 VS				P to A
2/2 VO				All locked

WV 700 series control valves - 3/3				
Function	Electromagnetic control	HR manual control	HF manual control	Neutral position
3/3 F				P and A to T
3/3 K				All locked
3/3 G				A locked P to T
3/3 GB				B locked P to

WV 700 series control valves - 3/2				
Function	Electromagnetic control	HR manual control	Electromagnetic HF manual	Neutral position
3/2 L				P locked A to T
3/2 N				P to A T locked

WV 700 series control valves - 4/3				
Function	Electromagnetic control	HR manual control	HF manual control	Neutral position
4/3 H				P A and B to T
4/3 E				All locked
4/3 P				A locked P and B to T
4/3 J				P locked A and B to T
4/3 M				P to a and B T locked
4/3 R				P and A to T B locked
4/3 U				P to T A and B locked

WV 700 series control valves - 4/2				
Function	Electromagnetic control	Electromagnetic control	Electromagnetic control	Neutral position
4/2 C				A to T P to B
4/2 D				P to A B to T